

VARIABLE DISPLACEMENT VANE PUMP WITH VARIABLE TARGET REGULATOR

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application claims the benefit of U.S. Provisional Application Serial No. 60/255,629, titled "Variable Displacement Pump and Method," filed December 12, 2000.

10 FIELD OF THE INVENTION

This invention relates generally to fluid pumps and more particularly to a variable displacement vane pump.

BACKGROUND OF THE INVENTION

15 Hydraulic power transmission assemblies and fluid distribution systems may utilize a vane-type pump. Such pumps typically have a rotor with a plurality of circumferentially spaced vanes rotatably carried by the rotor and slidable relative thereto in slots provided in the rotor. The rotor and vanes cooperate with the internal contour of a containment ring or eccentric ring eccentrically mounted relative to an
20 axis of the rotor and vanes to create fluid chambers between the containment ring or eccentric ring, rotor and vanes. Due to the eccentricity between the containment ring or eccentric ring and the rotor and vanes, the fluid chambers change in volume as they are moved with the rotating rotor and become larger in volume as they are moved across an inlet port and smaller in volume across an outlet port. To vary the
25 eccentricity between the containment ring or eccentric ring and the rotor, the containment ring or eccentric ring may be pivoted upon a fixed axis in a pump

housing. Pivoting the containment ring or eccentric ring varies the change in volume of the fluid chambers in use of the pump and hence, varies the displacement characteristic of the pump.

Side plates carried by the pump housing enclose the containment ring or eccentric ring, the rotor and the vanes, and provide passages through which fluid flows to and from the rotor and vanes. These passages, along with timing grooves and the containment ring or eccentric ring contour define pump cycles or zones, namely a fill or inlet zone, a precompression zone from the inlet to the outlet, a displacement or discharge zone, and a decompression zone from the outlet to the inlet.

In current vane-type pumps, the containment ring or eccentric ring is pivoted and oriented by a fluid pressure signal applied to a piston or directly to the containment ring which pivots the containment ring or eccentric ring against the bias of a fixed spring. In other words, a single fluid pressure signal is used to pivot the containment ring or eccentric ring. Accordingly, the control of the containment ring or eccentric ring is essentially limited to a pressure relief type control wherein the containment ring or eccentric ring is pivoted against the bias of the spring only when a sufficient pressure is applied to the piston or containment ring or eccentric ring. When the fluid pressure applied to the piston is not sufficient to move the containment ring or eccentric ring against the bias of a fixed spring, the position of the containment ring or eccentric ring is determined by the spring which limits to one regulation profile characteristic.

Additionally, it has been recognized that for efficient and quiet operation of a vane-type pump it is desirable to maintain the vanes in continuous contact with the

containment ring or eccentric ring. Some vane-type pumps depend upon centrifugal force to maintain the contact between the vanes and the containment ring or eccentric ring. These pumps may lack positive and continuous contact between the vane and containment ring or eccentric ring resulting in adverse wear and decreased pump performance. One method to improve the contact between the vanes and the containment ring or eccentric ring involves applying a discharge fluid pressure to chambers or slots in the rotor in which the vanes are received. The fluid pressure drives the vanes radially outwardly and into contact with the containment ring or eccentric ring. However, in at least some conditions, the vanes have a tendency to remain in the rotor slots and the centrifugal force of the spinning rotor is not sufficient to overcome the viscous drag force on the vanes. Without the vanes extending radially outwardly from the rotor, the rotating rotor displaces little if any fluid such that there is little or no discharge pressure. Accordingly, there is little or no discharge pressure communicated to the vane slots and tending to force the vanes radially outwardly from the rotor. Hence, the pump will not prime.

SUMMARY OF THE INVENTION

A variable displacement vane-type fluid pump is provided which has a regulated discharge controlled at least in part by a pair of pilot pressure signals. Desirably, the vane pump of the invention permits improved regulation of the pump discharge such that the pump can meet the various requirements of lubrication for internal combustion engines at all speeds. Of course, the vane pump may also be utilized in power transmission and other fluid distribution applications. The variable displacement vane pump of the invention may utilize both hydrostatic and

mechanical assistance in radially positioning its vanes to ensure efficient and quiet operation of the pump and to facilitate priming of the pump. The vane pump of the invention may also use both hydrostatic and mechanical actuators to control the position of its containment ring or eccentric ring and hence, regulate the output of the pump. According to yet another aspect of the present invention, to prevent inlet flow restriction or cavitation, a valve may be provided to permit some of the pump outlet or discharge flow to exhaust into the pump inlet to provide needed velocity energy to the fluid flow in the pump inlet.

To achieve the dual pilot pressure regulation of the pump output the vane pump has a pair of actuators each operable to position the containment ring or eccentric ring as desired. In one embodiment of the invention, the actuators are opposed pistons that are each actuated by a separate pilot pressure signal to pivot the cam as a function of the pressure signals. In another embodiment, a seal may be provided between the containment ring or eccentric ring and the pump housing defining separate chambers, the chambers receive pressurized fluid bearing directly on the containment ring or eccentric ring to position it and function as the actuators without any pistons between the fluid signal and the containment ring or eccentric ring. In any of the embodiments, the cam may be biased in one or both directions of its pivotal movement, such as by one or more springs.

To ensure priming of the pump and development of discharge pressure, one or more rings lie adjacent to the rotor radially inwardly of the vanes to ensure that at least some of the vanes extend radially outwardly beyond the rotor and in contact with the contoured ring at all times. Preferably, hydrostatic pressure is employed in

chambers behind the vanes to provide full extension of the vanes and maintain them in continuous contact with the containment ring or eccentric ring.

Accordingly, some of the objects, features and advantages of this invention include providing an eccentric vane pump which enables improved control of the pump discharge, ensures priming of the pump, reduces inlet flow restriction and cavitation, enables pressure signals from two or more points in the hydraulic circuit to be used to regulate pump discharge, strategically positions the cam and its pivot to minimize movement in the direction perpendicular to the desired direction of movement of the eccentric ring as it pivots, is of relatively simple design and economical manufacture and assembly, is durable, reliable and has a long and useful life in service.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects, features and advantages of this invention will be apparent from the following detailed description of the preferred embodiments, appending claims and accompanying drawings in which:

Fig. 1 is a perspective view of a variable displacement eccentric vane pump according to the present invention;

Fig. 2 is a perspective view of the vane pump of Fig. 1 with a side plate removed to show the internal components of the pump;

Fig. 3 is a plan view of the pump as in Fig. 2 illustrating the containment ring or eccentric ring in its zero-displacement position;

Fig. 4 is a plan view of the pump as in Fig. 2 illustrating the containment ring or eccentric ring in its maximum-displacement position;

Fig. 5 is a diagrammatic sectional view of a variable target dual pilot regulation valve which pivots the containment ring or eccentric ring of the pump according to one aspect of the present invention;

Fig. 6 is an enlarged, fragmentary sectional view illustrating a portion of the
5 rotor and a vane according to the present invention;

Fig. 7 is an enlarged, fragmentary sectional view of the rotor and vane illustrating a seal between the vane and rotor when the vane is tilted within its slot in the rotor;

Fig. 8 is a schematic representation of the hydraulic circuit of the vane pump
10 of an embodiment of this invention including completing a 3-way variable target dual pilot regulation valve;

Fig. 9 is a schematic representation of the hydraulic circuit of a vane pump according to the present invention including a 3-way variable target dual pilot regulation valve and an anti-cavitation valve; and

Fig. 10 is a diagrammatic view of the containment ring or eccentric ring of the
15 vane pump in its zero-displacement and maximum-displacement positions.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring in more detail to the drawings, Figs. 1 - 3 illustrate a variable
20 displacement vane pump 10 having a rotor 12 and associated vanes 14 driven for rotation to draw fluid through a pump inlet 16, increase the pressure of the fluid, and discharge the fluid under pressure from an outlet 18 of the pump 10. A containment ring or eccentric ring 20 is carried by a housing 22 of the pump 10 and is pivoted relative to the rotor 12 to vary the displacement of the pump. Such a pump 10 is

widely used in a plurality of fluid applications including engine lubrication and power transmission applications.

The housing 22 preferably comprises a central body 24 defining an internal chamber 26 in which the containment ring or eccentric ring 20 and rotor 12 are received. The housing 22 further includes a pair of end plates 28,30 on opposed, flat sides of the central body 24 to enclose the chamber 26. A groove 32 formed in an internal surface 34 of the central body 24 is constructed to receive a pivot pin 36 between the containment ring or eccentric ring 20 and housing 22 to permit and control pivotal movement of the containment ring or eccentric ring 20 relative to the housing 22. Spaced from the groove 32 and preferably at a generally diametrically opposed location, a seat surface 38 is provided in the central body 24. The seat surface 38 is engageable with the containment ring or eccentric ring 20 in at least certain positions of the containment ring or eccentric ring to provide a fluid tight seal between them. One or both of the containment ring or eccentric ring 20 and central body 24 may carry an elastomeric or other type seal 40 that defines at least in part the seat surface and reduces leakage between the containment ring or eccentric ring 20 and housing 22.

The containment ring or eccentric ring 20 is annular having an opening 41 and is received within the chamber 26 of the housing 22. The containment ring or eccentric ring 20 has a groove 42 in its exterior surface which receives in part the pivot pin 36 to permit pivotal movement between the containment ring or eccentric ring 20 and central body 24. Such pivotal movement of the containment ring or eccentric ring 20 is limited by engagement of the exterior surface of the containment ring or eccentric ring 20 with the interior surface 34 of the central body 24. As

viewed in Figs. 4 and 10, the containment ring or eccentric ring 20 is pivoted counterclockwise into engagement with the housing 22 in its first position wherein the pump 10 has its maximum displacement. As best shown in Figs 3 and 10, the containment ring or eccentric ring 20 may be pivoted clockwise from its first position to a second position in which the pump 10 has its minimum displacement. Of course, the containment ring or eccentric ring 20 may be operated in any orientation between and including its first and second positions to vary the displacement of the pump, as desired. The containment ring or eccentric ring 20 has an internal surface which is generally circular, but may be contoured or off-centered to improve or alter the pump 10 performance. The containment ring or eccentric ring 20 may also have a second groove 44 in its exterior surface adapted to carry the seal 40 engageable with the internal surface 34 of the central body 24 to provide a fluid tight seal between the containment ring or eccentric ring 20 and central body 24. The fluid tight seal essentially separates the chamber 26 into two portions 26a, 26b on either side of the seal to enable a pressure differential to be generated between the separated chamber portions 26a, 26b. The pressure differential may be used to pivot the containment ring or eccentric ring 20 between or to its first and second positions to control the pump displacement.

To move fluid through the pump 10, a rotating displacement group 50 is provided in the housing 22. The rotating displacement group 50 comprises a central drive shaft 52, the rotor 12 which is carried and driven for rotation by the drive shaft 52, and a plurality of vanes 14 slidably carried by the rotor 12 for co-rotation with the rotor 12. The drive shaft 52 is fixed in position for rotation about its own axis 53.

The rotor 12 is fixed to the drive shaft 52 for co-rotation therewith about the axis of the shaft 52.

As shown, the rotor 12 is a generally cylindrical member having a plurality of circumferentially spaced apart and axially and radially extending slots 54 that are open to an exterior surface 56 of the rotor 12 and which terminate inwardly of the exterior surface 56. Each slot 54 is constructed to slidably receive a separate vane 14 so that the vanes are movable relative to the rotor 12 between retracted and extended positions. Each slot 54 in the rotor 12 preferably terminates at a small chamber 58 constructed to receive pressurized fluid. The pressurized fluid in a chamber 58 acts on the vane 14 in the associated slot 54 to cause the vane 14 to slide radially outwardly until it engages the internal surface 34 of the containment ring or eccentric ring 20. Preferably, during operation of the pump 10, the fluid pressure within the chamber 58 and slot 54 is sufficient to maintain substantially continuous contact between the vanes 14 and the internal surface of the containment ring or eccentric ring 20.

In accordance with one aspect of the present invention, a vane extension member 60 is movably positioned on the rotor 12 to engage one or more of the vanes 14 and cause such vanes 14 to extend radially outwardly beyond the periphery of the rotor 12. This facilitates priming the pump 10 by ensuring that at least two of the vanes 14 extend beyond the periphery of the rotor 12 at all times. Without the extension member 60 the vanes 14 may tend to remain in their retracted position, not extending beyond the exterior 56 of the rotor 12, such that subsequent turning of the rotor 12 without any vanes 14 extending outwardly therefrom, does not displace sufficient fluid to prime the pump 10 and increase the pump output

pressure. Accordingly, no fluid pressure is generated in the chambers 58 or slots 54 of the rotor 12 and therefore no pressure acts on the vanes 14 causing them to extend outwardly and the pump 10 will not prime. Such a condition may be encountered, for example, in mobile and automotive applications when starting a cold vehicle in cold weather such as during a cold start of an automobile.

In the embodiment shown in Fig. 2, the vane extension member 60 is a ring slidably received in an annular recess 62 formed in an end face of the rotor 12 and having a diameter sufficient to ensure that at least two of the vanes 14 extends beyond the periphery of the rotor 12 at all times. The recess 62 provides an outer shoulder 64 and an inner shoulder 66 between which the ring 60 may slide. The ring 60 slides in the recess 62 when acted on by vanes 14 which are radially inwardly displaced via engagement with the containment ring or eccentric ring 20 thereby pushing the ring 60 towards the diametrically opposed vanes 14 causing them to extend beyond the periphery of the rotor 12. The ring 60 is retained between the rotor 12 and the adjacent side plate of the housing 22 in assembly of the pump 10. A second ring may be provided on the opposite face of the rotor, if desired.

Desirably, as shown in Figs. 6 and 7, the slots 54 in the rotor 12 are sized to permit a fluid film to form on the leading and trailing faces 68, 69 of each vane 14. The fluid film supports the vanes 14 as the rotor 12 rotates. The fluid film prevents a wear of the fluid slot effectively seating a bearing surface. Additionally, the size of the slots 54 is desired to prevent vane tilt while still slowing fluid to enter a contact seal between the rotor 12 and vanes 14 in the areas of their contact should vane tilting occur, to the extent that any vane tilting is present. The contact seals maintain the pressurized fluid acting on the vanes 14 and prevents it from leaking or flowing

out of the slots 54. Such leakage is otherwise likely to occur due to the pressure differential between the fluid in the chambers 58 and slots 54 which is at pump outlet pressure and lower pressure portions of the pump cycle (nearly all but at the outlet of the pump). By preventing this leakage, it is ensured that a sufficient hydrostatic force biases the vanes 14 radially outwardly toward the containment ring or eccentric ring 20 to improve the continuity of the contact between the vanes 14 and the containment ring or eccentric ring 20.

To displace fluid, the containment ring or eccentric ring 20 is mounted eccentrically relative to the drive shaft 52 and rotor 12. This eccentricity creates a varying clearance or gap between the containment ring or eccentric ring 20 and the rotor 12. The varying clearing creates fluid pumping chambers 70, between adjacent vanes 14, the rotor 12 and the internal surface of the containment ring or eccentric ring 20, which have a variable volume as they are rotated in use. Specifically, each pumping chamber 70 increases in volume during a portion of its rotational movement, thereby creating a drop in pressure in that pumping chamber 70 tending to draw fluid therein. After reaching a maximum volume, each pumping chamber 70 then begins to decrease in volume increasing the pressure therein until the pumping chamber is registered with an outlet and fluid is forced through said outlet at the discharge pressure of the pump 10. Thus, the eccentricity provides enlarging and decreasing pumping chambers 70 which provide both a decreased pressure to draw fluid in through the inlet of the pump 10 and thereafter increase the pressure of the fluid and discharge it from the outlet of the pump 10 under pressure.

The degree of the eccentricity determines the operational characteristics of the pump 10, with more eccentricity providing higher flow rate of the fluid through the

pump 10 and less eccentricity providing a lower flow rate in pressure of the fluid. In a so-called "zero displacement position" or the second position of the containment ring or eccentric ring 20 shown in Fig. 3, the opening 41 is essentially coaxially aligned with the rotor 12 so that the fluid pumping chambers 70 have an essentially constant volume throughout their rotation. In this orientation, the pumping chambers 70 do not enlarge to draw flow therein nor do they become smaller in volume to increase the pressure of fluid therein creating a minimum performance condition or a zero displacement condition of the pump 10. When the containment ring or eccentric ring 20 is in its first or maximum displacement position the pumping chambers 70 vary in size between their maximum volume and minimum volume as the rotor 12 rotates providing increased pump displacement.

As shown in Figs. 3 and 4, to control the pivoting and location of the containment ring or eccentric ring 20 a pair of pistons 72, 74 may be utilized with the pistons 72, 74 operable in opposed directions to pivot the containment ring or eccentric ring 20 between its first and second positions. Desirably, each piston 72, 74 may be responsive to different fluid pressure signals that may be taken from two different points in the fluid circuit, one of which must come from the regulating valve. Accordingly, two different portions of the fluid circuit may be used to control the displacement of the containment ring or eccentric ring 20, and hence the operation and displacement of the pump 10. The pistons 72, 74 may be of different sizes as desired to vary the force on the pistons from the pressurized fluid signals. Further, one or both of the pistons 72, 74 may be a spool type valve biased by a spring, or other mechanism to aid in controlling the movement of the containment ring or eccentric ring 20 and operation of the pump. As an alternative, if a seal 40 is

provided between the containment ring or eccentric ring 20 and housing 22, a controlled volume of fluid under pressure may be disposed directly in the chamber portions 26a, 26b defined on opposite sides of the seal 40. Fluid at different volumes and pressures may be provided on either side of the seal 40 to control the movement of the containment ring or eccentric ring 20. Of course, any combination of these actuators may be used to control the movement and position of the containment ring or eccentric ring 20 in use of the pump 10.

Desirably, as best shown in Fig. 10, in accordance with a further aspect of the present invention, the axis 76 about which the containment ring or eccentric ring 20 is pivoted is located to provide an essentially linear movement of the containment ring or eccentric ring 20 between its first and second positions. To do so, the containment ring or eccentric ring 20 is pivoted about an axis 76 which is offset from the drive shaft axis 53 by one-half of the distance of travel in the direction of eccentricity of the containment ring or eccentric ring 20 between its first and second positions. In other words, the pivot axis 76 of the containment ring or eccentric ring 20 is offset from the drive shaft axis 53 by one-half of the maximum eccentricity of the containment ring or eccentric ring 20 relative to the drive shaft axis 53, and hence, relative to the rotor 12. The pivoting movement of the containment ring or eccentric ring 20 occurs along an at least somewhat arcuate path. By positioning the pivot axis 76 of the containment ring or eccentric ring 20 as described, the path of movement of the containment ring or eccentric ring 20 becomes essentially linear between its first and second positions. Non-linear or compound movement of the containment ring or eccentric ring 20 affects the gap or clearance between the rotor 12 and the containment ring or eccentric ring 20. The performance and operating

characteristics of the pump 10 are determined by this gap or clearance. Accordingly, the non-linear movement of the containment ring or eccentric ring 20 when it is pivoted can vary the size of the fluid chambers throughout the pump 10, and importantly, in the area of the inlet 16 and outlet 18 of the pump. For example, the pumping chambers 70 may become slightly larger in volume as they approach the outlet 18 reducing the pressure of fluid therein and causing inefficient pressurization of the fluid at the discharge port. Desirably, offsetting the pivot axis 76 of the containment ring or eccentric ring 20 in accordance with this invention provides a movement of the containment ring or eccentric ring 20 which reduces such centrality errors and facilitates control of the pump operating characteristics to improve pump performance and efficiency. The arrangement of the invention also permits a more simple pump design with a center point of the containment ring or eccentric ring opening 41 moving along an essentially linear path. Further, the pump 10 should operate with less airborne or fluid borne noise.

Preferably, to control the application of fluid pressure signals to the actuators that in turn control the movement of the containment ring or eccentric ring 20, a single control valve 80 reacts to two pilot pressure signals and their application to the actuators. As shown in Fig. 5, the control valve 80 has a spool portion 82 with a plurality of annular grooves and lands between adjacent grooves providing sealing engagement with a bore 84 in which the spool portion 82 is received. The valve 80 also has a piston portion 86 comprising an outer sleeve 88 and an inner piston 90 slidably carried by the sleeve 88. A first spring 92 is disposed between the plunger 90 and the spool portion 82 to yieldably bias the position of the spool portion 82 and

a second spring 94 is disposed between the sleeve 88 and the plunger 90 to yieldably bias the plunger 90 away from the sleeve 88.

As shown in Figs. 5 and 8, the valve 80 has a first inlet 96 through which fluid discharged from the pump 10 is communicated with a chamber 98 in which the plunger 90 is received to provide a force acting on the plunger 90 in a direction opposing the biasing force of the second spring 94. A second inlet 100 communicates fluid discharged from the pump 10 with the spool portion 82. A third inlet 102 communicates fluid pressure from a downstream fluid circuit source from a second portion of the fluid circuit with a chamber 104 defined between the plunger 90 and outer sleeve 88. A fourth inlet 106 communicates the second portion of the fluid circuit with an end 108 of the spool portion 82 located opposite the plunger 90. In addition to the inlets, the valve 80 has a first outlet 110 communicating with a sump or reservoir 112, a second outlet 114 communicating with the first actuator 74, and a third outlet 116 communicating with the second actuator 72. As discussed above, the first and second actuators 72, 74 control movement of the containment ring or eccentric ring 20 to vary the displacement of the pump 10.

In more detail, the plunger 90 has a cylindrical body 120 with a blind bore 122 therein to receive and retain one end of the first spring 92. An enlarged head 124 at one end of the plunger 90 is closely slidably received in the chamber 98, which may be formed in, for example, the pump housing 22, and is constructed to engage the outer sleeve 88 to limit movement of the plunger 90 in that direction. The outer sleeve 88 is preferably press-fit or otherwise fixed against movement in the chamber 98. The outer sleeve 88 has a bore 126 which slidably receives the body 120 of the plunger 90, a radially inwardly extending rim 128 at one end to limit movement of the

spool portion 82 toward the plunger 90, and a reduced diameter opposite end 130 defining the annular chamber 104 in which the second spring 94 is received. The annular chamber 104 may also receive fluid under pressure which acts on the plunger 90.

5 The spool portion 82 is generally cylindrical and is received in the bore 84 of a body, such as the pump housing 22. The spool portion 82 has a blind bore 132, is open at one end 134 and is closed at its other end 108. A first recess 136 in the exterior of the spool portion 82 leads to one or more passages 138 which open into the blind bore 132. The first recess 136 is selectively aligned with the third outlet 10 116 to permit the controlled volume of pressurized fluid, keeping the displacement high at the second actuator 72 to vent back through the spool portion 82 via the first recess 136, corresponding passages 138, blind bore 132 and the first outlet 110 15 leading to the sump or reservoir 112. This reduces the volume and pressure of fluid at the second actuator 72. Likewise, the spool portion 82 has a second recess 140 which leads to corresponding passages 142 opening into the blind bore 132 and which is selectively alignable with the second outlet 114 to permit fluid controlled volume of pressurized fluid, keeping the displacement low at the first actuator 74 to vent back through the valve 80 via the second recess 140, corresponding passages 142, blind bore 132 and first outlet 110 to the sump or reservoir 112.

20 The spool portion 82 also has a third recess 144 disposed between the first and second recesses 136, 140 and generally aligned with the second inlet 100. The third recess 144 has an axial length greater than the distance between the second inlet 100 and the second outlet 114 and greater than the distance between the second inlet 100 and the third outlet 116. Accordingly, when the spool portion 82 is

sufficiently displaced toward the plunger portion 86, the third recess 144 communicates the second outlet 114 with the second inlet 100 to enable fluid at discharge pressure to flow through the second outlet 114 from the second inlet 100. This increases the volume of pressure and fluid acting on the first actuator 74.

5 Likewise, when the spool portion 82 is displaced sufficiently away from the plunger portion 86, the third recess 144 communicates the second inlet 100 with the third outlet 116 to permit fluid at pump discharge pressure to flow through the third outlet 116 from the second inlet 100. This increases volume of pressure and fluid acting on the second actuator 72. From the above it can be seen that displacement of the
10 spool portion 82 controls venting of the displacement control chamber through the first and second recesses 136, 140, respectively, when they are aligned with the second and third outlets 114, 116, respectively. Displacement of the spool portion 82 also permits charging or increasing of the pilot pressure signals through the third recess 144 when it is aligned with the second and third outlets 114, 116,
15 respectively.

Desirably, the displacement of the spool portion 82 may be controlled at least in part by two separate fluid signals from two separate portions of the fluid circuit. As shown, fluid at pump discharge pressure is provided to chamber 98 so that it is applied to the head 124 of the plunger 90 and tends to displace the plunger 90
20 toward the spool portion 82. This provides a force (transmitted through the first spring 92) tending to displace the spool portion 82. This force is countered, at least in part, by the second spring 94 and the fluid pressure signal from a second point in the fluid circuit which is applied to the distal end 108 of the spool portion 82 and to the chamber 104 between the outer sleeve 88 and plunger 90 which acts on the

head 124 of the plunger 90 in a direction tending to separate the plunger from the outer sleeve. The movement of the spool portion 82 can be controlled as desired by choosing appropriate springs 92, 94, fluid pressure signals and/or relative surface areas of the plunger head 124 and spool portion end 108 upon which the pressure signals act. Desirably, to facilitate calibration of the valve 80, the second spring 94 may be selected to control the initial or at rest compression of the first spring 92 to control the force it applies to the spool portion 82 and plunger 90.

In response to these various forces provided by the springs 92, 94 and the fluid pressure signals acting on the plunger 90 and the spool portion 82, the spool portion 82 is moved to register desired recesses with desired inlet or outlet ports to control the flow of fluid to and from the first and second actuators 72, 74. More specifically, as viewed in Fig. 5, when the spool portion 82 is driven downwardly, the third recess 144 bridges the gap between the second inlet 100 and the third outlet 116 so that pressurized fluid discharged from the pump 10 is provided to the second actuator 72. This movement of the spool portion 82 preferably also aligns the second recess 140 with the second outlet 114 to vent the volume and pressure of fluid at the first actuator 74 to the sump or reservoir 112. Accordingly, the containment ring or eccentric ring 20 will be displaced by the second actuator 72 toward its first position increasing the displacement of the pump 10. As the spool portion 82 is driven upwardly, as viewed in Fig. 5, the third recess 144 will bridge the gap between the second inlet 100 and the second outlet 114 providing fluid at pump discharge pressure to the first actuator 74. This movement of the spool portion 82 preferably also aligns the first recess 136 with the third outlet 116 to vent the volume of and pressure of fluid at the second actuator 72 to the sump or reservoir 112.

Accordingly, the containment ring or eccentric ring 20 will be moved toward its second position decreasing the displacement of the pump 10. In this manner, the relative controlled volume and pressures are controlled by two separate pressure signals which may be taken from two different portions of the fluid circuit. In the embodiment shown, a first pressure signal is the fluid discharged from the pump 10 and a second pressure signal is from a downstream fluid circuit source. In this manner, the efficiency and performance of the pump can be improved.

As best shown in Fig. 9, an inlet flow valve 150 in the fluid circuit may be provided to selectively permit fluid at pump discharge pressure to flow back into the pump inlet 16 when the pump 10 is operating at speeds wherein atmospheric pressure is insufficient to fill the pump 10 with fluid. This reduces cavitation and overcome any restriction of fluid flow to the inlet 16 of the pump 10. To accomplish this, the inlet flow valve 150 may be a spool type valve slidably received in a bore 152 of a body, such as the pump housing 22, so that it is in communication with the fluid discharged from the pump outlet 18. As shown, the fluid circuit comprises the pump 10, with the pump outlet 18 leading to an engine lubrication circuit 154 through a supply passage 156 which passes through the bore 152 containing the inlet flow valve 150. Downstream of the engine lubrication circuit 154, fluid is returned to a reservoir 112 with a portion of such fluid routed through a pilot fluid passage 158 leading to the inlet flow valve 150 to provide a pilot pressure signal on the inlet flow valve 150, if desired. A spring 159 may also be provided to bias the inlet flow valve 150. From the reservoir, fluid is supplied through an inlet passage 160 to the inlet 16 of the fuel pump 10. The inlet passage 160 can pass through the bore 152 containing the inlet flow valve 150 and is separated from the supply passage 156 by

a land 162 of the inlet flow valve 150 which provides an essentially fluid tight seal with the body.

Accordingly, the fluid discharged from the pump 10 acts on the land 162 by way of passage 156 in communication with from outlet line 157 and tends to displace the inlet flow valve 150 in a direction opposed by the spring 159 and the pilot pressure signal applied to the inlet flow valve 150 through the pilot fluid passage 158. When the pressure of fluid discharged from the pump 10 is high enough, to overcome the spring and pilot pressure from passage 158, the inlet flow valve 150 will be displaced so that its land 162 will be moved far enough to open the inlet passage 160 permitting communication between the supply passage 156 and inlet passage 160 through the bore 152 and passage 161, as shown in Fig. 9. Thus, a portion of the fluid discharged from the pump 10 is fed back into the inlet 16 of the pump 10 along with fluid supplied from the reservoir 112 for the reasons stated above. This aspirated flow of pressurized fluid into the inlet 16 supercharges the pump inlet to ensure that the pump 10 is pumping liquid and not air or gas. This prevents cavitation and improves the pump efficiency and performance.

The purpose of the valve 150 and its supercharging effect is to convert pressure energy and convert it to velocity energy at the inlet to provide supercharging.

Accordingly, the pump 10 incorporates many features which facilitate the design and operation of the pump, enable vastly improved control over the pump operating parameters and output, and improve overall pump performance and efficiency. Desirably, the vane pump of the invention can meet the various requirements of lubrication for internal combustion engines at all speeds. Of course,

the vane pump may also be utilized in power transmission and other fluid distribution applications.

Finally, while preferred embodiments of the invention have been described in some detail herein, the scope of the invention is defined by the claims which follow.

- 5 Modifications of and applications for the inventive pump which are entirely within the spirit and scope of the invention will be readily apparent to those skilled in the art.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202